


# Narrow V-Belts


- For drives where compact design is required, higher speed is necessary and increased horsepower needed
- Effective for installations where overall drive cost must be reduced
- Narrower and lighter sheaves reduce weight load and overhang on bearings resulting in decreased bearing loads
- Transmits greater horsepower than Conventional V-belts in the same drive space
- Heat and oil resistant, static conductive


## BELT NUMBER SIGNIFICANCE

**5V 1320**

5V = Cross Section  
1320 = Outside Length, 132.0 in.

 TW = 3/8 in - 9.5 mm H = 5/16 in - 7.9 mm	Belt No.	Outside Length	Weight Lbs.	Belt No.	Outside Length	Weight Lbs.	Belt No.	Outside Length	Weight Lbs.
	3V 250	25.0	0.1	3V 475	47.5	0.2	3V 900	90.0	0.4
3V 265	26.5	0.1	3V 500	50.0	0.2	3V 950	95.0	0.4	
3V 280	28.0	0.1	3V 530	53.0	0.2	3V1000	100.0	0.4	
3V 300	30.0	0.1	3V 560	56.0	0.2	3V1060	106.0	0.5	
3V 315	31.5	0.1	3V 600	60.0	0.3	3V1120	112.0	0.5	
3V 335	33.5	0.2	3V 630	63.0	0.3	3V1180	118.0	0.6	
3V 355	35.5	0.2	3V 670	67.0	0.3	3V1250	125.0	0.6	
3V 375	37.5	0.2	3V 710	71.0	0.3	3V1320	132.0	0.7	
3V 400	40.0	0.2	3V 750	75.0	0.3	3V1400	140.0	0.7	
3V 425	42.5	0.2	3V 800	80.0	0.4				
3V 450	45.0	0.2	3V 850	85.0	0.4				

 TW = 5/8 in - 15.9 mm H = 17/32 in - 13.5 mm	Belt No.	Outside Length	Weight Lbs.	Belt No.	Outside Length	Weight Lbs.	Belt No.	Outside Length	Weight Lbs.
	5V 500	50.0	0.6	5V1000	100.0	1.2	5V2000	200.0	2.4
5V 530	53.0	0.7	5V1060	106.0	1.2	5V2120	212.0	2.5	
5V 560	56.0	0.7	5V1120	112.0	1.3	5V2240	224.0	2.7	
5V 600	60.0	0.7	5V1180	118.0	1.4	5V2360	236.0	2.8	
5V 630	63.0	0.7	5V1250	125.0	1.5	5V2500	250.0	3.0	
5V 670	67.0	0.8	5V1320	132.0	1.6	5V2650	265.0	3.2	
5V 710	71.0	0.8	5V1400	140.0	1.7	5V2800	280.0	3.3	
5V 750	75.0	0.8	5V1500	150.0	1.8	5V3000	300.0	3.6	
5V 800	80.0	0.9	5V1600	160.0	1.9	5V3150	315.0	3.8	
5V 850	85.0	0.9	5V1700	170.0	2.0	5V3350	335.0	4.0	
5V 900	90.0	1.1	5V1800	180.0	2.1	5V3550	355.0	4.3	
5V 950	95.0	1.1	5V1900	190.0	2.3				

 TW = 1 in - 25.4 mm H = 3/8 in - 22.2 mm	Belt No.	Outside Length	Weight Lbs.	Belt No.	Outside Length	Weight Lbs.	Belt No.	Outside Length	Weight Lbs.
	8V1000	100.0	3.5	8V1800	180.0	6.3	8V3150	315.0	11.1
8V1060	106.0	3.7	8V1900	190.0	6.7	8V3350	335.0	11.8	
8V1120	112.0	3.9	8V2000	200.0	7.0	8V3550	355.0	12.5	
8V1180	118.0	4.2	8V2120	212.0	7.5	8V3750	375.0	13.7	
8V1250	125.0	4.4	8V2240	224.0	7.9	8V4000	400.0	14.0	
8V1320	132.0	4.6	8V2360	236.0	8.3	8V4250	425.0	14.9	
8V1400	140.0	4.9	8V2500	250.0	8.8	8V4500	450.0	15.8	
8V1500	150.0	5.3	8V2650	265.0	9.3	8V4750	475.0	16.7	
8V1600	160.0	5.6	8V2800	280.0	9.8	8V5000	500.0	17.6	
8V1700	170.0	6.0	8V3000	300.0	10.5				