

Double Angle Belts

- For drives where power must be transmitted by both the top and bottom of the belt
- Belts flex equally well in both directions for positive pulley contact
- Good for serpentine or reverse bend drives
- Oil and heat resistant, static conductive

BELT NUMBER SIGNIFICANCE

AA 105 AA = Double Angle A Section
105 = Nominal Length, 105 in.

AA

Belt No.	Outside Length	Pitch Length	Weight Lbs.	Belt No.	Outside Length	Pitch Length	Weight Lbs.	Belt No.	Outside Length	Pitch Length	Weight Lbs.
AA 51	54.4	53.1	0.40	AA 73	76.4	75.1	0.63	AA 96	99.4	98.1	0.80
AA 55	58.4	57.1	0.45	AA 75	78.4	77.1	0.65	AA 105	108.4	107.1	0.90
AA 60	63.4	62.1	0.50	AA 78	81.4	80.1	0.68	AA 107	110.4	109.1	0.90
AA 62	65.4	64.1	0.51	AA 80	83.4	82.1	0.70	AA 112	115.4	114.1	0.95
AA 64	67.4	66.1	0.53	AA 84	87.4	86.1	0.78	AA 120	123.4	122.1	1.00
AA 66	69.4	68.1	0.54	AA 85	88.4	87.1	0.80	AA 128	131.4	130.1	1.10
AA 68	71.4	70.1	0.60	AA 90	93.4	92.1	0.80				
AA 70	73.4	72.1	0.60	AA 92	95.4	94.1	0.80				

BB

Belt No.	Outside Length	Pitch Length	Weight Lbs.	Belt No.	Outside Length	Pitch Length	Weight Lbs.	Belt No.	Outside Length	Pitch Length	Weight Lbs.
BB 43	47.6	45.9	0.64	BB 96	100.6	98.9	1.30	BB 162	166.6	164.9	2.15
BB 45	49.6	47.9	0.66	BB 97	101.6	99.9	1.30	BB 168	172.6	170.9	2.20
BB 51	55.6	53.9	0.75	BB 103	107.6	105.9	1.40	BB 169	173.6	171.9	2.20
BB 53	57.6	55.9	0.78	BB 105	109.6	107.9	1.40	BB 173	177.6	175.9	2.30
BB 54	58.6	56.9	0.80	BB 107	111.6	109.9	1.50	BB 180	184.6	182.9	2.40
BB 55	59.6	57.9	0.80	BB 108	112.6	110.9	1.50	BB 182	186.6	184.9	2.40
BB 60	64.6	62.9	0.80	BB 111	115.6	113.9	1.50	BB 190	194.6	192.9	2.60
BB 68	72.6	70.9	0.90	BB 112	116.6	114.9	1.50	BB 195	199.6	197.9	2.60
BB 71	75.6	73.9	0.94	BB 116	120.6	118.9	1.60	BB 210	214.6	212.9	2.80
BB 72	76.6	74.9	0.95	BB 117	121.6	119.9	1.60	BB 225	228.1	226.4	3.00
BB 73	77.6	75.9	0.96	BB 118	122.6	120.9	1.60	BB 226	229.1	227.4	3.00
BB 74	78.6	76.9	1.00	BB 119	123.6	121.9	1.60	BB 228	231.1	229.4	3.00
BB 75	79.6	77.9	1.00	BB 120	124.6	122.9	1.60	BB 230	233.1	231.4	3.10
BB 76	80.6	78.9	1.00	BB 123	127.6	125.9	1.70	BB 240	243.1	241.4	3.20
BB 77	81.6	79.9	1.10	BB 124	128.6	126.9	1.70	BB 255	258.1	256.4	3.35
BB 78	82.6	80.9	1.10	BB 128	132.6	130.9	1.80	BB 267	270.1	268.4	3.50
BB 81	85.6	83.9	1.10	BB 129	133.6	131.9	1.80	BB 270	273.1	271.4	3.60
BB 83	87.6	85.9	1.10	BB 130	134.6	132.9	1.80	BB 273	276.1	274.4	3.60
BB 85	89.6	87.9	1.20	BB 136	140.6	138.9	1.90	BB 277	280.1	278.4	3.70
BB 90	94.6	92.9	1.20	BB 140	144.6	142.9	1.95	BB 278	281.1	279.4	3.70
BB 92	96.6	94.9	1.25	BB 144	148.6	146.9	2.00	BB 285	288.1	286.4	3.80
BB 93	97.6	95.9	1.30	BB 155	159.6	157.9	2.10	BB 300	303.1	301.4	4.00
BB 94	98.6	96.9	1.30	BB 157	161.6	159.9	2.10	BB 330	333.1	331.4	4.30
BB 95	99.6	97.9	1.30	BB 158	162.6	160.9	2.10				

CC

Belt No.	Outside Length	Pitch Length	Weight Lbs.	Belt No.	Outside Length	Pitch Length	Weight Lbs.	Belt No.	Outside Length	Pitch Length	Weight Lbs.
CC 75	81.4	79.2	1.70	CC 128	134.4	132.2	3.20	CC 221	227.4	225.2	5.40
CC 81	87.4	85.2	1.90	CC 136	142.4	140.2	3.40	CC 225	229.4	227.2	5.50
CC 85	91.4	89.2	2.00	CC 144	150.4	148.2	3.60	CC 240	244.4	242.2	5.80
CC 90	96.4	94.2	2.20	CC 148	154.4	152.2	3.70	CC 255	259.4	257.2	6.16
CC 96	102.4	100.2	2.40	CC 158	164.4	162.2	3.80	CC 270	274.4	272.2	6.50
CC 105	111.4	109.2	2.60	CC 162	168.4	166.2	3.90	CC 300	304.4	302.2	7.20
CC 112	118.4	116.2	2.80	CC 173	179.4	177.2	4.20	CC 330	334.4	332.2	7.90
CC 119	125.4	123.2	2.97	CC 180	186.4	184.2	4.40	CC 360	364.4	362.2	8.70
CC 120	126.4	124.2	3.00	CC 195	201.4	199.2	4.70	CC 390	394.4	392.2	9.50
CC 125	131.4	129.2	3.10	CC 210	216.4	214.2	5.10	CC 420	424.4	422.2	10.20