

FLEXIBLE COUPLINGS







BODY

SPIDER

BODY

INTERCHANGEABLE WITH LOVEJOY COUPLINGS.

Series	*Capacity At 1200 RPM	*Capacity At 3600 RPM	Outside Diameter	Overall Length Complete	Use Spider
FC 070	.72	2.16	1-3/8"	2"	B070
FC075	1.44	4.32	1-3/4"	2-1/8"	B075
FC090	2.40	7.20	2-1/8"	2-5/16"	B090
FC095	3.40	10.10	2-1/8"	2-3/4"	B090
FC099	5.00	15.10	2-9/16"	2-13/16"	B099
FC100	7.20	21.60	2-9/16"	3-1/2"	B099
FC110	13.20	39.60	3-15/16"	4-1/4"	B110

^{*} Capacity is calculated with a service factor of 1.0 and with Buna-N inserts.

AVAILABLE IN THE FOLLOWING BORE SIZES:

Bore Size	FC070	FC075	FC090	FC095	FC099	FC100	FC110
1/2",	х	Х	X	Х		Х	
5/8"	Х	Х	Х	X T	Х	Х	Х
3/4"	Х	X	Х	Χ.	Х	Х	X
7/8"		X	Х	Х	Х	X	X
1"		2	a. x	Х	Х	Х	Х
1-1/8"				Х	Х	Х	X
1-1/4"						Х	Х
1-3/8"						Х	Х
1-1/2"							Х
1-5/8"							X

X DESIGNATES ITEMS AS STANDARD STOCK

NOTE: To interchange with LoveJoy eliminate "FC" prefix and add "L".

EXAMPLE:

Coupling FC090x1/2" interchangeable with L090x1/2" LoveJoy.